

CAMSO

ATV T4S

All work, all play, all seasons

An ATV track system that has built its solid reputation thanks to great performance across all conditions.

Experience optimal effectiveness all year long, no matter the weather and your vehicle type.



MACHINE

300^{CC} TO
1000^{CC}



ALL-TERRAIN



SPECIFICATIONS

RUBBER TRACK	
Width	Front: 11.5 in. (292 mm) Rear: 12.5 in. (318 mm)
Length	Front: 93.4 in. (2372 mm) Rear: 98.5 in. (2507 mm)
Lug height	Front: 1.25 (32 mm) Rear: 1.25 in. (32 mm)
Rubber track	Front: flex Rear: flat
PERFORMANCE	
Ground surface	2000 sq. in. (1.30 m ²)
Maintained speed (average)	2/3

Please find more specifications on page 20

INDUSTRY'S FIRST

Flex-Track design

Front-mounted tracks with flexible sides and slight curve toward the inside

- Stable handling
- More comfortable ride than traditional flat tracks
- Precise steering for pleasant long-distance riding and long working hours

Bearing housing

Outer seals and stainless steel sleeves

- Enduring bearing durability
- Greater reliability

Solid steel frame

Open light-weight design

- Proven durability and performance
- Easily sheds snow, mud, and debris

Idler and mid-roller wheels

Sealed wheel and bearing with elastomeric outer band

- Provides a longer life in rough conditions
- 100% ice-free

Tandem stabilizer

Bolt-on tandem mid-roller wheel

- Provides a smoother ride by absorbing shocks

Cap

Fitted wheel cap with bladder effect

- Eliminates water absorption due to temperature variations

