# TRAILED TRACK SYSTEMS

CAMSO

ROAD FREE COMPANY

FORMERLY
CAMOPLAST
SOLIDEAL





# REDUCES COMPACTION ZONES FOR IMPROVED PERFORMANCE

The Camso Trailed Track System increases the performance of high capacity AG application equipment.

Its large footprint distributes the weight of heavier, high capacity carts and toolbars and reduces ground pressure between 30% to 80% compared to tires.

The Camso TTS eliminates multi-tire contact points to just two track contact points per pass in the field, thus reducing the number of pinch row effects. The exclusive double oscillating bogie suspension maintains maximum ground contact by reducing point loading conditions to the soil structure.

**LESS COMPACTION ZONES IN THE FIELD ALLOW FOR BETTER WATER AND NUTRIENT ABSORPTION RESULTING IN HIGHER PRODUCING CROPS. THE CAMSO TRAILED TRACK SYSTEM HELPS GET YOU THERE.**

# TRAILED TRACK SYSTEMS



# THE RIGHT TRACK SYSTEM FOR YOUR APPLICATION



## CAMSO TTS 30/40

### Increase your mobility

This small frame series is uniquely designed to provide a large footprint in a small undercarriage package for superior flotation when compared to tires. The perfect choice for planters, fertilizer carts, and sprayers.

**PERFORMANCE**

FLOTATION

RIDE QUALITY

MAINTENANCE FREE



## CAMSO TTS 70/80/100

### Performs with the lowest ground pressure

This large frame series is designed for larger footprints allowing higher weight capacity and low ground pressure performance. Provides low rolling and turning resistance for ease of pulling. The perfect choice for large capacity planters, fertilizer carts, and harvest carts.

**PERFORMANCE**

FLOTATION

RIDE QUALITY

MAINTENANCE FREE

# TRAILED TRACK SYSTEMS

**Every stage covered, from planting to harvesting**



TTS 30



TTS 40



TTS 70



TTS 80/100/110

## Tension system

**Ensures proper operation of the system without any additional adjustments or maintenance**

- Mechanical spring track tensioner actively maintains tension

## Track

**Reduces ridging or berming on headlands**

- Designed exclusively for trailed applications
- Lowers rolling resistance for ease of pulling

## Alignment system

**Simplifies the alignment process to support long track life**

- Swing link design with push/pull adjusters and positive locking feature



## Wheels

**Reduced maintenance — no greasing or repacking of bearings**

- Stamped, steel wheel construction for increased strength
- Heavy duty wheel hubs with oil bath lubrication

## Main frames

**Increased durability**

- Strong and rigid frame design

## Suspension system

**Maintains greater ground contact and support on uneven terrain**

- Improves cart stability and product placement
- Patented double oscillating bogie wheels

# HARVEST CARTS

## Achieves lower compaction on one of the heaviest tools in the field



- Reduces ground pressure by 50 – 85% versus tires
- Low rolling and turning resistance for ease of pulling

| TTS Models | Track Width (in) | Overall Height (in) | Overall Length (in) | Ground Contact - Per Pair (in²) | Capacity - Per Pair (lbs) |
|---|---|---|---|---|---|
| 70-3611 | 36.0 | 35.7 | 103.1 | 4,850 | 70,000 |
| 80-3013 | 30.0 | 39.9 | 135.8 | 6,010 | 80,000 |
| 100-3613 | 36.0 | 39.9 | 135.8 | 7,210 | 100,000 |
| 110-3614 | 36.0 | 39.9 | 147.0 | 8,010 | 110,000 |

# FERTILIZER CARTS

## Improves cart stability and product placement



- Reduces ground pressure up to 60% versus tires
- Narrow track widths available for row crop applications

| TTS Models | Track Width (in) | Overall Height (in) | Overall Length (in) | Ground Contact - Per Pair (in²) | Capacity - Per Pair (lbs) |
|---|---|---|---|---|---|
| 30-1611 | 16.5 | 35.6 | 80.8 | 1,580 | 30,000 |
| **40-1511** | **15.0** | **40.4** | **104.4** | **2,170** | **40,000** |
| **45-1815** | **18.0** | **40.4** | **104.4** | **2,610** | **45,000** |
| 100-3613 | 36.0 | 39.9 | 135.8 | 7,210 | 100,000 |



# PLANTERS, STRIP TILL, SEED CARTS

## Reduces compaction zones for improved planter performance



- Lowers ground pressure 40 –60% versus tires
- Increases field mobility and performs with minimal disturbance on headlands
- Impacts fewer rows by replacing 4 tire contact points with 2-track solution

| TTS Models | Track Width (in) | Overall Height (in) | Overall Length (in) | Ground Contact - Per Pair (in²) | Capacity - Per Pair (lbs) |
|---|---|---|---|---|---|
| 30-1611 | 16.5 | 35.6 | 80.8 | 1,580 | 30,000 |
| 30-1612 | 16.5 | 30.5 | 72.7 | 1,390 | 30,000 |
| 35-1813 | 18.0 | 30.5 | 72.7 | 1,520 | 35,000 |
| 35-2011 | 20.0 | 30.5 | 72.7 | 1,690 | 35,000 |
| 35-2211 | 22.0 | 30.5 | 72.7 | 1,860 | 35,000 |
| 35-2511 | 25.0 | 30.5 | 72.7 | 2,110 | 35,000 |
| **40-1511** | **15.0** | **40.4** | **104.4** | **2,170** | **40,000** |
| **45-1815** | **18.0** | **40.4** | **104.4** | **2,610** | **45,000** |
| 40-2512 | 25.0 | 35.6 | 80.8 | 2,390 | 40,000 |
| 70-2516 | 25.0 | 35.7 | 103.1 | 3,370 | 70,000 |
| 70-3011 | 30.0 | 35.7 | 103.1 | 4,040 | 70,000 |
| 70-3611 | 36.0 | 35.7 | 103.1 | 4,850 | 70,000 |

# SPRAYERS

## Gains field access when the time is right



- Achieves 10 x more footprint than row crop tires
- Improves cart stability and boom placement versus wheeled versions

| TTS Models | Track Width (in) | Overall Height (in) | Overall Length (in) | Ground Contact - Per Pair (in²) | Capacity - Per Pair (lbs) |
|---|---|---|---|---|---|
| 30-1611 | 16.5 | 35.6 | 80.8 | 1,580 | 30,000 |
| **40-1511** | **15.0** | **40.4** | **104.4** | **2,170** | **40,000** |
| **45-1815** | **18.0** | **40.4** | **104.4** | **2,610** | **45,000** |

Camso provides comprehensive warranty coverage for a period of 12 months from date of purchase, for Trailed Track Systems (TTS), against defects in materials and workmanship. Some conditions apply. Refer to the warranty certificate for details. For more info, visit **camso.co/agriculture**




We are dedicated to our clients and customers. For the AG customer service, contact us toll free at 1 844 CAMSOAG, or 1 317 671-7327, or by email at Ag.ProductSupport@camso.co

## Connect with us for exclusive Road Free content

@camso.co @camso_co @camso_co

**camso.co**

CAMSO

ROAD FREE COMPANY

FORMERLY CAMOPLAST SOLIDEAL